Adopted

Rejected

COMMITTEE REPORT

YES: 10 NO: 0

MR. SPEAKER:

15

IC 9-19-6-1.5.

Your Committee on Roads and Transportation, to which was referred House Bill has had the same under consideration and begs leave to report the same back to the House with the recommendation that said bill be amended as follows:

```
1
            Page 2, line 27, delete "at its own cost,".
            Page 2, line 30, after "maintenance." insert "The cost of the
 3
         maintenance may be wholly or partially borne by the department,
 4
         county, city, or town upon agreement with the railroad.".
 5
            Page 2, delete lines 31 through 35.
            Page 2, line 36, delete "(g)" and insert "(f)".
 6
 7
            Page 2, line 39, delete "(h)" and insert "(g)".
 8
            Page 2, line 41, delete "(i):" and insert "(h):".
 9
            Page 3, line 4, delete "(i)" and insert "(h)".
10
            Page 3, after line 11, begin a new paragraph and insert:
            "SECTION 2. IC 9-13-2-117.7 IS ADDED TO THE INDIANA
11
         CODE AS A NEW SECTION TO READ AS FOLLOWS
12
13
         [EFFECTIVE JULY 1, 2005]: Sec. 117.7. "Operating crew
14
         member", for purposes of IC 9-19-6, has the meaning set forth in
```

CR149501/DI 96+

1 SECTION 3. IC 9-19-6-1.5 IS ADDED TO THE INDIANA CODE 2 AS A NEW SECTION TO READ AS FOLLOWS [EFFECTIVE 3 JULY 1, 2005]: Sec. 1.5. "Operating crew member" has the 4 meaning set forth in IC 8-9-12-2. 5 SECTION 4. IC 9-19-6-19 IS AMENDED TO READ AS FOLLOWS [EFFECTIVE JULY 1, 2005]: Sec. 19. (a) A vehicle may be equipped with lamps that may be used for the purpose of warning 8 the operators of other vehicles of the presence of a vehicular traffic 9 hazard requiring the exercise of unusual care in approaching, 10 overtaking, or passing. The vehicles, when so equipped, may display 11 the warning in addition to any other warning signals required by this 12 article. 13 (b) A lamp used to display a warning to the front must be mounted 14 at the same level and as widely spaced laterally as practicable, and must 15 display simultaneously flashing white or amber lights or any shade of 16 color between white and amber. 17 (c) A lamp used to display a warning to the rear must be mounted at 18 the same level and as widely spaced laterally as practicable, and must show simultaneously flashing amber or red lights or any shade of color 19 20 between red and amber. 21 (d) A warning light must be visible from a distance of not less than 22 five hundred (500) feet under normal atmospheric conditions at night. 23 (e) A motor vehicle used to transport operating crew members 24 may display a lamp placed on the top of the motor vehicle with 25 simultaneously flashing yellow or amber lights that must be visible

27 Renumber all SECTIONS consecutively.
(Reference is to HB 1495 as introduced.)

as set forth in subsection (d).".

and when so amended that said bill do pass.

26

Representative Duncan

CR149501/DI 96+ 2005